



10 Reasons to Choose U2-Pro Ink Jet Printer

Comparison Items	U2-Pro Ink Jet Printer	CIJ Continuous Ink Jet
1. Lower printer cost	✓	-
2. Higher print resolution (600DPI)	✓	-
3. No consumable parts	✓	-
4. No-maintenance	✓	-
5. No technician required	✓	-
6. Environmental friendly (no MEK required)	✓	-
7. Easy-to-operate	✓	-
8. Easy-to-integrate	✓	-
9. Wide printable substrates	✓	✓
10. Lower total cost of ownership	✓	-

U2TM
PRO

Small yet powerful. Say goodbye to CIJ!

- **1/3 the cost**
- **1/30 the size**
- **Zero-maintenance**





U2-Pro Specifications:

Display	3.5" Color LCD with LED backlight
User-interface	Simple and easy-to-use operating system
Input Device	Pocket-sized IR remote keypad
Available Languages	English, Japanese, French, German, Spanish, Portuguese, Russian, Korean, Italian, Turkish, Hungarian, Slovak, Czech, Swedish, Romanian, Serbian, Bulgarian, Chinese (Traditional & Simplified)
LED Indicators	Alarm, Ink low, print, run, remote on/off
Print Engine	Funai-Lexmark Thermal Ink Jet technology
Print Resolution & Print Speed	600 x 300 dpi (76.2 m/min) Print quality is resolution & speed dependent.
Print Distance	Recommended 6mm
Print Height	Up to 4 lines and 12.7mm (0.5"). Selectable font size from 2.7mm, 3.6mm, 5.5mm, 8mm, 10mm, 12.7mm
Print Capability	Alphanumeric, logos, date/time, shift code, counter, lot box code
Barcodes	EAN8, EAN13, EAN14, EAN128, UPCA, UPCE, CODE39, CODE128, TF14 (SCC-14), NVE18 (SSCC-18), C25INTER, CODABAR, PDF417, DATAMATRIX, QRCODE
Electrical Requirements	AC 100V~240V, 50/60Hz
Weight	0.571kg (1.21 lb.) - excluding cartridge and bracket
Dimensions (L/W/H)	119.2x77.7x77 (mm)
Mounting Orientation	Horizontal or downside
Message Storage Capacity	Store up to 999 messages
Operating Temperature	5°C – 40°C (41°F – 104°F)
Data Interface	RS485 & USB port

Optional Accessories:

Encoder	Provide high print quality on unstable conveyor
Photocell	Provide more reliable and precise sensing parameter
Alarm Kit	Alert users in the event of an incident



WWW.ANSER-U2.COM